1 Clifton Range 2 YEARS



1. Nickel Electro Clifton NE1V Oven Incubators

The NE1V oven/incubators provide a stable temperature environment for general purpose applications, and features a digital PID controller for precision. The controls feature an auto alarm, and the insulated chamber and door ensures low energy consumption.

- Dual temperature display, actual and set values
- Stainless steel chamber
- Gravity convection chamber
- Exhaust outlet
- Single insulated door, lockable
- Silicone door chamber seal
- Anti-bacterial paint exterior
- Stackable
- Levelling feet, adjustable at each corner
- Factory two point calibration, 37°C and 150°C
- Temperature range: ambient +5 to 250°C
- Temperature fluctuation (@37/150°C): ±0.3/±0.5°C
- Temperature variation (@37/150°C): ±1/±2°C

Code	Capacity, L	Supplied with	Shelf Positions	Int Dims, w x d x h, mm	Ext Dims, w x d x h, mm	Pack	Price
OVE1018	32	1 wire shelf	2	400 x 270 x 320	740 x 460 x 560	Each	**£1118.10**
OVE6840	56	2 wire shelves	4	400 x 390 x 360	740 x 610 x 600	Each	**£1189.16**

2 LAB PRO 2 YEARS



2. SLS Lab Pro Fan Convection Ovens

Chamber bright polished stainless steel lagged with high efficiency thermal insulation. Digital temperature control up to 250°C with program feature run back timer. Over temperature auto set and over temperature protection. Single insulated door, lockable with 2 point door engagement for an even seal.

- Door chime when left open
- Anti-bacterial paint finish
- Temperature range: ambient +5 to 250°C
- Over temperature alarm is automatically set 5°C above set point for incubator protection, automatic reset
- PID digital LED display showing actual or set temperature, resolution 0.1°C
- Temperature fluctuation ±0.4 @ 37°C, measurements based on temperature readings on shelf in centre of the chamber
- Temperature variation ±1.8 @ 37°C, measured in vertical axis in the chamber
- Run back timer with indicator and end messaging 00:01 to 99:59 (hh:mm)
- Fan convection from 0% variable to 100% for forced air circulation
- Temperature sensor fail alarm with error reporting
- Perforated stainless steel shelves included with adjustable runners

Code	Capacity, L	No. of Shelves	Shelf Positions	Int Dims, w x d x h, mm	Ext Dims, w x d x h, mm	Pack	Price
OVE9016	30	1	3	400 x 250 x 320	600 x 460 x 630	Each	**£1458.96**
OVE9010	60	2	5	400 x 400 x 360	600 x 605 x 720	Each	**£1649.26**