



Code	Capacity, L	No. of Shelves	Dims, w x d x h, mm	Pack	Price
OVE2068	30	2	500 x 490 x 560	Each	£912.50
OVE2070	40	2	500 x 490 x 640	Each	£995.57
OVE2072	53	2	630 x 470 x 650	Each	£1060.68
OVE2074	73	2	630 x 600 x 650	Each	£1182.36
OVE2076	99	3	630 x 600 x 770	Each	£1272.97
OVE2078	121	3	630 x 600 x 870	Each	£1391.74
OVE2080	143	3	630 x 680 x 870	Each	£1527.26
OVE2082	180	4	630 x 800 x 1070	Each	£1947.13

1. Genlab Multi-Purpose Benchtop Ovens

A range of highly efficient, reliable and cost effective ovens to suit most warming, drying and heat treatment processes. Available in a variety of sizes and designed with base mounted displays to suit your exact needs. Featuring the latest touch screen control system which offers intuitive control and excellent accuracies designed for industrial and laboratory ovens. The exterior is constructed from sheet steel and finished in an easy clean powder coated paint. The interior chamber is made from mild steel coated with aluminium (CLAD). Heated by Incoloy sheathed elements; positioned in the base of the oven on all natural convection ranges.

- Temp range: 40 to 250°C
- On screen historical trending (48 hours)
- Manual or automatic overheat reset
- High accuracy Pt100B duplex sensors <0.8°C
- Excellent stability <±0.6°C
- Low chamber uniformity



Code	Description	Capacity, L	No. of Shelves	Dims, w x d x h, mm	Pack	Price
INC2008	MINI/6/TDIG	6	1	350 x 330 x 460	Each	£775.89
INC2010	MINI/18/TDIG	18	1	380 x 410 x 550	Each	£821.41
INC2012	MINI/30/TDIG	30	2	480 x 490 x 510	Each	£814.95
INC2014	MINI/40/TDIG	40	2	480 x 490 x 540	Each	£839.98
INC2016	MINI/50/TDIG	53	2	630 x 470 x 660	Each	£979.95
INC2018	MINI/75/TDIG	73	2	630 x 600 x 660	Each	£1182.36
INC2020	MINI/100/TDIG	99	3	630 x 600 x 780	Each	£1272.97

2. Genlab Multi-Purpose Benchtop Incubator

The Genlab range of benchtop incubators offers a range of highly efficient, reliable and cost effective units to suit most biological analysis, research and general laboratory applications. Available in a variety of sizes to suit your exact needs. Featuring the latest touch screen control system which offers intuitive control and excellent accuracies designed for industrial and laboratory incubators. The exterior is constructed from sheet steel and finished in an easy clean powder coated paint. The interior chamber is made from either mild steel coated with aluminium (CLAD) or a stainless steel (SS) chamber. They are fitted with fixed shelf runners and removable chrome plated wire grid shelves.

- Temp range ambient: +5°C to 70°C
- Fluctuation ±0.25 °C at 37 °C
- High resolution 0.1°C
- On screen historical trending (48 hours)
- Manual or automatic overheat reset
- High accuracy Pt100B duplex sensors <0.8°C
- Excellent stability <±0.6°C
- Low chamber uniformity