

1. Genlab Dual Purpose Benchtop Incubator/Ovens

The Genlab range of dual purpose ovens / incubators combine the advantage of two temperature ranges in the same unit. Using bespoke firmware designed specifically for this chamber size, and a calibration class temperature sensor, we can offer accurate control up to 250°C without temperature overshoot. The same chamber can also maintain a steady 30°C constant temperature by simply adjusting the set point. Available in a variety of sizes and designed with both side and base mounted display options, to suit your exact needs.

- 10 sizes 6 to 200 litres (base mount controller design)
- 6 sizes 50 to 200 litres (side mount controller design)
- Temp range: ambient +8°C to 250°C
- Resolution 0.1°C
- On screen historical trending (48 hours)
- Manual or automatic overheat reset
- High accuracy Pt100A duplex sensors <math><0.6^{\circ}\text{C}</math>
- Excellent stability $\pm 0.6^{\circ}\text{C}$



Code	Description	Capacity, L	No. of Shelves	No. of Places	Dims, w x d x h, mm	Pack	Price
INC2242	MINIS/6/TDIG	6	1	1	320 x 330 x 390	Each	£678.86
INC2244	MINIS/18/TDIG	18	1	1	380 x 410 x 520	Each	£739.73
INC2246	MINIS/30/TDIG	30	2	2	500 x 490 x 560	Each	£771.75
INC2248	MINIS/40/DIG	40	2	3	500 x 490 x 640	Each	£870.81
INC2250	MINIS/50/DIG	53	2	3	630 x 470 x 650	Each	£927.00
INC2252	MINIS/75/DIG	73	2	3	630 x 600 x 650	Each	£1072.14

2. Genlab Multi-Purpose Benchtop Ovens

The Genlab range of benchtop ovens offers a range of highly efficient, reliable and cost effective ovens to suit most warming, drying and heat treatment processes. Available in a variety of sizes and designed with base mounted displays to suit your exact needs. Featuring our latest touch screen control system which offers intuitive control and excellent accuracies designed for industrial and laboratory ovens. The exterior is constructed from sheet steel and finished in an easy clean powder coated paint. The interior chamber is made from mild steel coated with aluminium (CLAD). Heated by Incoloy sheathed elements; positioned in the base of the oven on all natural convection ranges.

- 10 sizes 6 to 200 litres (base mount controller design)
- Temp range 40°C to 250°C
- On screen historical trending (48 hours)
- Manual or automatic overheat reset
- High accuracy Pt100B duplex sensors <math><0.8^{\circ}\text{C}</math>
- Excellent stability $\pm 0.6^{\circ}\text{C}$
- Low chamber uniformity



Code	Capacity, L	No. of Shelves	No. of Places	Dims, w x d x h, mm	Pack	Price
OVE2068	30	2	2	500 x 490 x 560	Each	£738.39
OVE2070	40	2	3	500 x 490 x 640	Each	£792.54
OVE2072	53	2	3	630 x 470 x 650	Each	£844.44
OVE2074	73	2	3	630 x 600 x 650	Each	£952.76
OVE2076	99	3	4	630 x 600 x 770	Each	£1048.04
OVE2078	121	3	5	630 x 600 x 870	Each	£1136.92
OVE2080	143	3	5	630 x 680 x 870	Each	£1262.40
OVE2082	180	4	7	630 x 800 x 1070	Each	£1610.15