# SLS Select Education - Safety Data Sheet

CHE2102SE

(in accordance with regulation (EU) 2015/830 and regulation (EC) 1272/2008)

Revision: 2.1 Revision date: 16 April 2021
Date printed: 25 January 2022

# **Section 1. Identification**

1.1 Product Identifier CHE2102SE

Product Name HEXAN-1-OL pure 500ml.

CAS Number 111-27-3

REACH Registration No 01-2119487967-12-XXXX

Molecular Formula CH<sub>3</sub> (CH<sub>2</sub>) CH<sub>2</sub> OH =102.18

## 1.2 Relevent identified uses of the substance or mixure & uses advised against

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

#### 1.3 Supplier SLS Select Education



Wilford Industrial Estate

Ruddington Lane

Wilford Nottingham NG11 7EP

UNITED KINGDOM

Phone 0115 9821111 Fax 0115 9825275

Email sales@scientific-labs.com

## **1.4 Emergency Telephone** (08:00-17:00) 0115 9821111

(24hr) 112 (Have this document to hand)

# Section 2. Hazards Identification

# 2.1 Classification of the substance or mixture

## Classification according to regulation 1272/2008/EC

Flammable liquid, category 3 Acute toxicity, category 4 (oral) Acute toxicity, category 4 (dermal) Serious eye damage/irritation, category 2 H226: Flammable liquid and vapour.

H302: Harmful if swallowed.

H312: Harmful in contact with skin.

H319: Causes serious eye irritation.

## 2.2 Label elements

## Labelling according to regulation 1272/2008/EC

Signal word Warning

Hazard Pictograms





Hazard Statements Flammable liquid and vapour. Causes serious eye irritation. Harmful if swallowed. Harmful in contact with skin.

**Precautionary Statements** Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed.

Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Wash thoroughly after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. IF ON SKIN: Wash with plenty of soap and water.

## **Section 3. Composition**

#### 3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
Hexan-1-ol	111-27-3	203-852-3	01-2119487967-12-XXXX	>95%	Flam. Liq. 3,Acute Tox. 4 (O),Acute Tox. 4 (D),Eye Irrit. 2

# Section 4. First Aid

## 4.1 Description of first aid measures

Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL Eyes

ATTENTION UKGENTLY.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately avoiding contamination of

unaffected areas.

Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If Inhalation

breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery

position. OBTAIN MEDICAL ATTENTION URGENTLY.

If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen Ingestion

if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first Wear protective gloves / eye protection.

aiders

### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

## **Section 5. Fire Fighting**

### 5.1 Extinguishing media

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed

containers cool.

Unsuitable Media Do not use water jet.

#### 5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

## 5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear

protective clothing and breathing apparatus.

## Section 6. Accidental Release Measures

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate Personal Protection

area immediately. Do not allow general use of area until it is safe to do so. Beware: vapour is heavier than air and

will tend to accumulate at low spots.

### 6.2 Environmental precautions

Enviromental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local

Ref: CHE2102SE

Environmental Health Officer if major spillage occurs.

#### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with

copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in

remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

#### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

# Section 7. Storage & Handling

#### 7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

## 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage. Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

### 7.3 Specific end use(s)

See section 1.2.

# Section 8. Workplace Exposure & Personal Protection

### 8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits				
			Long Term (8hr TWA)		Short Term 15min period)		
Hexan-1-ol	111-27-3	>95%	-	-	-	-	

Exposure data source(s) No occupational exposure data currently available.

### 8.2 Exposure controls

maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

# Section 9. Physical & Chemical Properties

## 9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Pungent.
pH Not applicable
Boiling Point 157°C Approx.

Melting Point -52°C

Flash Point 57°C (Closed cup)

Upper Flammable Limit 7.7%
Lower Flammable Limit 1.2%
Auto Ignition 293°C
Explosive Properties Slight.
Oxidising Properties No.

Vapour Pressure 0.75mmHg @ 20°C

Relative Density 0.8250

Water Solubility Insoluble in water.

## 9.2 Other information

No data available.

# Section 10. Stability & Reactivity

10.1 Reactivity No data available.

10.2 Chemical Stability Stable under normal conditions

10.3 Possibility of hazardous

reactions

No data available.

10.4 Conditions to Avoid Hot surfaces, naked flames or other sources of ignition.

10.5 Incompatable Materials Acids. Strong oxidising agents.

Hazardous Decomposition None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Products

# **Section 11. Toxicological Information**

#### 11.1 Information on toxicological effects

The liquid may cause severe irritation and corneal damage. High concentrations of vapour may cause severe Eyes

irritation.

Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Liquid can be absorbed Skin

through intact skin. Very significant absorbtion can lead to collapse and may even prove fatal.

LD50 Skin 1500 - 2000mg/kg Rabbit

Harmful if swallowed. Ingestion may cause central nervous system depression, leading to unconsciousness. Ingestion

Symptoms may include salivation, thirst, difficulty in swallowing, pain, shock and vomiting.

LD50 Oral 720mg/kg Rat

Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes and Inhalation

respiratory tract. High concentrations of vapour may effect the central nervous system acting as a narcotic.

LD50 Inhalation Not available TCLo Not available

Carcinogenicity Not considered to be a carcinogen. Mutagenicity Not considered to be a mutagen.

Reproductive Effects None identified.

# Section 12. Ecological

12.1 Toxicity Readily bio-degraded in the environment.

LC50 Algal 11.3mg/l Green algae (72 hours) LC50 Crustacea 201mg/l Daphnia magna (24 hours) LC50 Fish 97mg/l Fathead Minnow (96 hours)

12.2 Persistence and Readily bio-degraded in the environment. degradability

**12.3** Bioaccumulative potential No data available. **12.4** Mobility in soil No data available.

Results of PBT & vPvB Assessment not required.

assessment

Other adverse effects None known at present.

# **Section 13. Disposal Considerations**

#### 13.1 Waste treatment methods

Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of Disposal Methods

into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

# Section 14. Transport Information

14.1 UN Number 2282 14.2 Proper Shipping Name Hexanols


14.3 Transport classes

UN classification 3 Subsidiary hazard(s) None Transport category 3 ADR Hazard ID 30 **Tunnel Restriction Code** D/E 14.4 Packing Group Ш

14.5 Environment hazards See section 12.

14.6 Special precautions for No special precautions required.

14.7 Transport in bulk Not transported in bulk.



15.1 Safety, health and environment regulations specific for subtance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 3; Acute toxicity, category 4 (oral); Acute toxicity, category 4 (dermal); Serious eye

damage/irritation, category 2

Signal word Warning

Hazard Pictograms





**Hazard Statements** H226, H319, H302, H312

Flammable liquid and vapour. Causes serious eye irritation. Harmful if swallowed. Harmful in contact with skin.

Precautionary Statements P210, P233, P240, P243, P264, P305+P351+P338, P302+P352

> Keep away from heat / sparks/open flames/hot surfaces - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Wash thoroughly after handling. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if

present and easy to do and continue rinsing. IF ON SKIN: Wash with plenty of soap and water.

## 15.2 Chemical safety assessment

Assessment not required.

# Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 2.1 (Supercedes revision 2.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 25 January 2022

Copyright: 2022 SLS Select Education