

**Section 1. Identification****1.1 Product Identifier** CHE2846SE

Product Name PHENOLPHTHALEIN SOLUTION 500ml.

CAS Number Mixture

REACH Registration No A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.

**1.2 Relevant identified uses of the substance or mixture & uses advised against**

Uses of Material Chemical for industrial and laboratory use. Not suitable for domestic use.

**1.3 Supplier** SLS Select EducationWilford Industrial Estate  
Ruddington Lane  
Wilford  
Nottingham  
NG11 7EP  
UNITED KINGDOM

Phone 0115 9821111

Fax 0115 9825275

Email sales@scientific-labs.com

**1.4 Emergency Telephone** (08:00-17:00) 0115 9821111  
(24hr) 112  
(Have this document to hand)**Section 2. Hazards Identification****2.1 Classification of the substance or mixture****Classification according to regulation 1272/2008/EC**

Flammable liquid, category 2

Serious eye damage/irritation, category 2

Germ cell mutagenicity, category 2

Carcinogenicity, category 1B

H225: Highly flammable liquid and vapour.

H319: Causes serious eye irritation.

H341: Suspected of causing genetic defects.

H350: May cause cancer.

**2.2 Label elements****Labelling according to regulation 1272/2008/EC**

Signal word Danger

Hazard Pictograms



Hazard Statements Highly flammable liquid and vapour. Suspected of causing genetic defects. May cause cancer. Causes serious eye irritation.

Precautionary Statements Obtain special instructions before use. Avoid release to the environment. Wear protective gloves / protective clothing / eye protection / face protection. IF exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing.

## Section 3. Composition

### 3.2 Mixtures

| Component          | CAS No. | EEC No.   | REACH No.             | Conc w/w | CLP Classification (1272/2008/CE)     |
|--------------------|---------|-----------|-----------------------|----------|---------------------------------------|
| Ethanol Industrial | 64-17-5 | 200-578-6 | 01-2119457610-43-XXXX | 47.5%    | Flam. Liq. 2, Eye Irrit. 2, STOT SE 2 |
| Phenolphthalein    | 77-09-8 | 201-004-7 |                       | 1%       | Muta. 2, Carc. 1B, Repr. 2            |

## Section 4. First Aid

### 4.1 Description of first aid measures

Eyes Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.

Skin Wash off skin thoroughly with water. Remove contaminated clothing immediately and wash before re-use.

Inhalation Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Ingestion If conscious give plenty of water to drink. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.

Personal protection for first aiders Wear protective gloves / eye protection.

### 4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

### 4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

## Section 5. Fire Fighting

### 5.1 Extinguishing media

Extinguishing Media Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.

Unsuitable Media Do not use water jet.

### 5.2 Special hazards arising from the substance or mixture

Hazards Vapour-air mixtures are explosive.

### 5.3 Advice for firefighters

Advice for firefighters Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.

## Section 6. Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.

### 6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

### 6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

### 6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

## Section 7. Storage & Handling

### 7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

### 7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

### 7.3 Specific end use(s)

See section 1.2.

## Section 8. Workplace Exposure & Personal Protection

### 8.1 Control parameters

| Component          | CAS No  | Concentration | Workplace Exposure Limits |                         |   |   |
|--------------------|---------|---------------|---------------------------|-------------------------|---|---|
|                    |         |               | Long Term (8hr TWA)       | Short Term 15min period |   |   |
| Ethanol Industrial | 64-17-5 | 47.5%         | 1000.0 ppm                | 1920.0 mg/m-3           | - | - |
| Phenolphthalein    | 77-09-8 | 1%            | -                         | -                       | - | - |

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

### 8.2 Exposure controls

Respiratory Protection Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

## Section 9. Physical & Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Fresh and characteristic.

pH Not applicable

Boiling Point Not available

Melting Point Not applicable

Flash Point 24°C (Closed cup)

Upper Flammable Limit Not applicable

Lower Flammable Limit Not applicable

Auto Ignition Not applicable

Explosive Properties Moderate/severe in confined spaces.

|                      |                               |
|----------------------|-------------------------------|
| Oxidising Properties | No.                           |
| Vapour Pressure      | Not applicable                |
| Relative Density     | Not available                 |
| Water Solubility     | Completely miscible in water. |

## 9.2 Other information

No data available.

## Section 10. Stability & Reactivity

|   |   |
|---|---|
| 10.1 Reactivity                         | No data available.  |
| 10.2 Chemical Stability                 | Stable under normal conditions  |
| 10.3 Possibility of hazardous reactions | No data available.  |
| 10.4 Conditions to Avoid                | Hot surfaces, naked flames or other sources of ignition.  |
| 10.5 Incompatible Materials             | Strong oxidising agents. Nitric acid. Silver nitrate, potassium perchlorate, chromyl chloride, chromium trioxide and permanganic acid. Peroxides, potassium permanganate, sodium, potassium, platinum, potassium tertiary butoxide. |
| 10.6 Hazardous Decomposition Products   | None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.  |

## Section 11. Toxicological Information

### 11.1 Information on toxicological effects

|                      |  |
|----------------------|--|
| Eyes                 | The liquid will cause conjunctival irritation and corneal damage. High concentrations of vapour may be irritating to the eyes.   |
| Skin                 | Repeated or prolonged contact may defat the skin producing irritation and dermatitis. Unlikely to be absorbed across the skin in harmful amounts.  |
| LD50 Skin            | Not available  |
| Ingestion            | Low order of acute toxicity. Fatal dose in man 300-400ml. Ingestion of large amounts will produce central nervous system depression. Symptoms may include nausea, vomiting muscular incoordination and loss of consciousness. Aspiration during swallowing or vomiting may injure lungs.   |
| LD50 Oral            | Not available  |
| Inhalation           | Exposure to vapour concentrations above the occupational exposure limits may produce irritation of the eyes and respiratory tract. High concentrations of vapour may produce central nervous system depression and unconsciousness. Symptoms will be similar to those following ingestion. |
| LD50 Inhalation      | Not available  |
| TCLo                 | Not available  |
| Carcinogenicity      | Not considered to be a carcinogen.   |
| Mutagenicity         | Not considered to be a mutagen.  |
| Reproductive Effects | Some evidence for foetotoxicity and tetragenecity has been observed in experimental animals treated with high doses of ethanol during gestation.   |
| Other Information    | Contains methanol. This will not constitute a special problem since ethanol is preferentially metabolised. Chronic intoxication may however produce damage to the optic nerve.   |

## Section 12. Ecological

|                                    |  |
|------------------------------------|--|
| 12.1 Toxicity                      | Ethanol is readily biodegradable after 15 days in non-acclimated fresh water. 75% biodegradability occurs after 20 days in salt water. |
| LC50 Algal                         | Not available  |
| LC50 Crustacea                     | Not available  |
| LC50 Fish                          | Not available  |
| 12.2 Persistence and degradability | No data available.   |
| 12.3 Bioaccumulative potential     | No data available.   |
| 12.4 Mobility in soil              | No data available.   |

12.5 Results of PBT & vPvB assessment      Assessment not required.

12.6 Other adverse effects      None known at present.

## Section 13. Disposal Considerations

### 13.1 Waste treatment methods

Disposal Methods      Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.

Contaminated Packaging      Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

## Section 14. Transport Information

14.1 UN Number      1170

14.2 Proper Shipping Name      Ethanol solution

14.3 Transport classes

UN classification      3

Subsidiary hazard(s)      None

Transport category      3

ADR Hazard ID      30

Tunnel Restriction Code      D/E

14.4 Packing Group      III

14.5 Environment hazards      See section 12.

14.6 Special precautions for user      No special precautions required.

14.7 Transport in bulk      Not transported in bulk.



## Section 15. Regulatory Information

### 15.1 Safety, health and environment regulations specific for substance/mixture.

#### Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification      Flammable liquid, category 2; Serious eye damage/irritation, category 2; Germ cell mutagenicity, category 2; Carcinogenicity, category 1B

Signal word      Danger

Hazard Pictograms



Hazard Statements      H225, H341, H350, H319  
Highly flammable liquid and vapour. Suspected of causing genetic defects. May cause cancer. Causes serious eye irritation.

Precautionary Statements      P201, P273, P280, P308+P313, P305+P351+P338  
Obtain special instructions before use. Avoid release to the environment. Wear protective gloves / protective clothing / eye protection / face protection. IF exposed or concerned: Get medical advice/attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing.

### 15.2 Chemical safety assessment

Assessment not required.

## Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.2 (Supercedes revision 1.1)

Revision date: 29 April 2021

Reviewed by chemist: 29 April 2021

Printed date: 25 January 2022

Copyright: 2022 SLS Select Education