

Section 1. Identification**1.1 Product Identifier**

CHE5814SE

Product Name

PENTAN-2-OL 100ml.

CAS Number

Mixture

REACH Registration No

A registration number is not available as the substance or its uses are exempt, the annual tonnage does not require a registration or the registration is envisaged for a later date.

1.2 Relevant identified uses of the substance or mixture & uses advised against

Uses of Material

Chemical for industrial and laboratory use. Not suitable for domestic use.

1.3 Supplier

SLS Select Education



Wilford Industrial Estate
Ruddington Lane
Wilford
Nottingham
NG11 7EP
UNITED KINGDOM

Phone

0115 9821111

Fax

0115 9825275

Email

sales@scientific-labs.com

1.4 Emergency Telephone

(08:00-17:00) 0115 9821111
(24hr) 112
(Have this document to hand)

Section 2. Hazards Identification**2.1 Classification of the substance or mixture****Classification according to regulation 1272/2008/EC**

Flammable liquid, category 3

Skin corrosion/irritation, category 2

Acute toxicity, category 4 (inhalation)

Serious eye damage/irritation, category 2

Spec target organ tox - single, category 3

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H319: Causes serious eye irritation.

H335: May cause respiratory irritation.

2.2 Label elements**Labelling according to regulation 1272/2008/EC**

Signal word

Warning

Hazard Pictograms



Hazard Statements Flammable liquid and vapour. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.

Precautionary Statements Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection / face protection. Use only outdoors or in a well-ventilated area. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Store in a well ventilated place. Keep container tightly closed. IF ON SKIN: Wash with plenty of soap and water.

Section 3. Composition

3.1 Substances

Component	CAS No.	EEC No.	REACH No.	Conc w/w	CLP Classification (1272/2008/CE)
PENTAN-2-OL				>98%	Flam. Liq. 3, Skin Irrit. 2, Acute Tox. 4 (I), Eye Irrit. 2, STOT SE 3 (I)

Section 4. First Aid

4.1 Description of first aid measures

Eyes	Irrigate thoroughly with plenty of water for at least 10 minutes, holding the eye open. OBTAIN MEDICAL ATTENTION URGENTLY.
Skin	Wash off skin thoroughly with water. Remove contaminated clothing immediately avoiding contamination of unaffected areas.
Inhalation	Remove from exposure. Keep warm and at rest. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Ingestion	If conscious give plenty of water to drink. Rinse mouth. Do not induce vomiting. If there is difficulty in breathing give oxygen if available. If breathing stops or shows signs of failing, apply artificial resuscitation. If unconscious place in the recovery position. OBTAIN MEDICAL ATTENTION URGENTLY.
Personal protection for first aiders	Wear protective gloves / eye protection.

4.2 Most important symptoms and effects, both acute & delayed.

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed.

No further relevant information available.

Section 5. Fire Fighting

5.1 Extinguishing media

Extinguishing Media	Water spray, alcohol resistant foam, dry powder or carbon dioxide. Use water spray to keep fire exposed containers cool.
Unsuitable Media	Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards	Vapour-air mixtures are explosive.
---------	------------------------------------

5.3 Advice for firefighters

Advice for firefighters	Evacuate area immediately. Keep up wind. Avoid exposure to toxic vapours and fumes. Fire-fighters should wear protective clothing and breathing apparatus.
-------------------------	--

Section 6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal Protection	Ensure no sources of ignition. Avoid breathing vapour. Use approved personal protective equipment. Evacuate area immediately. Do not allow general use of area until it is safe to do so. Beware : vapour is heavier than air and will tend to accumulate at low spots.
---------------------	---

6.2 Environmental precautions

Environmental Keep material out of sewers, storm drains, surface waters and soil. Notify the Environmental Agency and local Environmental Health Officer if major spillage occurs.

6.3 Methods and material for containment and cleaning up

Major Spillage Contain and absorb on inert material. Transfer absorbent to salvage container for removal. Wash area down with copious amounts of water.

Minor Spillage Contain and absorb on inert material. Transfer absorbent to container for removal. Allow solvent to evaporate in remote area, then dispose of absorbent as solid chemical waste. Wash area down with copious amounts of water.

6.4 Reference to other sections

See section 8.2 for information on protective equipment and section 13 for information on disposal.

Section 7. Storage & Handling

7.1 Precautions for safe handling

All transfer systems should be earthed to prevent accumulation of static electricity. Avoid contact with skin and eyes. Do not breath vapours. Do not allow to contaminate clothing.

Ensure Local Exhaust Ventilation maintains vapour concentrations below the recommended limits.

7.2 Conditions for safe storage, including any incompatibilities

Well ventilated, cool, dry storage . Protect from direct sun and store away from sources of ignition. Keep containers closed when not in use. Keep well separated from oxidising agents.

7.3 Specific end use(s)

See section 1.2.

Section 8. Workplace Exposure & Personal Protection

8.1 Control parameters

Component	CAS No	Concentration	Workplace Exposure Limits	
			Long Term (8hr TWA)	Short Term 15min period
PENTAN-2-OL		>98%	-	-

Exposure data source(s) IOELV: Indicative Occupational Exposure Limit Value.

8.2 Exposure controls

Respiratory Protection Use L.E.V. or natural ventilation to maintain vapour concentrations below exposure limits. If not, use a well maintained chemical cartridge organic vapour respirator, or use self contained breathing apparatus.

Hand Protection Use solvent resistant gloves.

Eye Protection Use tightly fitting chemical splash proof glasses or goggles.

Skin Protection Avoid contact with skin. If skin contact or contamination of clothing is likely, protective clothing must be worn.

Special Hazards No special precautions required.

Section 9. Physical & Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance Clear colourless liquid.

Odour Not available

pH Not applicable

Boiling Point 118 - 119 °C

Melting Point - 73 °C

Flash Point Not applicable

Upper Flammable Limit 9 %(V)

Lower Flammable Limit 1.2 %(V)

Auto Ignition Not applicable

Explosive Properties Slight.

Oxidising Properties	No.
Vapour Pressure	Not applicable
Relative Density	Not available
Water Solubility	Not available

9.2 Other information

No data available.

Section 10. Stability & Reactivity

10.1 Reactivity	No data available.
10.2 Chemical Stability	Stable under normal conditions
10.3 Possibility of hazardous reactions	No data available.
10.4 Conditions to Avoid	Hot surfaces, naked flames or other sources of ignition.
10.5 Incompatible Materials	Acids. Strong oxidising agents.
10.6 Hazardous Decomposition Products	None unusual. Burning will produce smoke, carbon monoxide and/or carbon dioxide.

Section 11. Toxicological Information

11.1 Information on toxicological effects

Eyes	The liquid, solutions and vapour are irritating to the eyes.
Skin	The liquid, solutions and vapour are irritating to the skin.
LD50 Skin	Not available
Ingestion	Harmful if swallowed. Ingestion may cause central nervous system depression, leading to unconsciousness. Symptoms may include salivation, thirst, difficulty in swallowing, pain, shock and vomiting.
LD50 Oral	2.821 mg/kg Rabbit
Inhalation	Exposure to vapour concentrations above the occupational exposure limits will produce irritation of the eyes and respiratory tract. High concentrations of vapour may effect the central nervous system acting as a narcotic.
LD50 Inhalation	Not available
TCLo	Not available
Carcinogenicity	Not considered to be a carcinogen.
Mutagenicity	Not considered to be a mutagen.
Reproductive Effects	None identified.

Section 12. Ecological

12.1 Toxicity	Readily bio-degraded in the environment.
LC50 Algal	Not available
LC50 Crustacea	Not available
LC50 Fish	Not available
12.2 Persistence and degradability	None known at present.
12.3 Bioaccumulative potential	No data available.
12.4 Mobility in soil	No data available.
12.5 Results of PBT & vPvB assessment	None unusual.
12.6 Other adverse effects	None known at present.

Section 13. Disposal Considerations

13.1 Waste treatment methods

Disposal Methods	Dispose of in a licensed incinerator for organic solvents. Do not dispose of as domestic waste. Never dispose of into water courses or sewerage systems due to high risk of explosion.
Contaminated Packaging	Use a licensed waste disposer. Do not attempt to burn any residual liquids due to risk of explosion.

Section 14. Transport Information

14.1 UN Number	1105
14.2 Proper Shipping Name	Pentanol
14.3 Transport classes	
UN classification	3
Subsidiary hazard(s)	None
Transport category	3
ADR Hazard ID	30
Tunnel Restriction Code	D/E
14.4 Packing Group	III
14.5 Environment hazards	See section 12.
14.6 Special precautions for user	No special precautions required.
14.7 Transport in bulk	Not transported in bulk.



Section 15. Regulatory Information

15.1 Safety, health and environment regulations specific for substance/mixture.

Classification, Labeling & Packaging of Substances & Mixtures Regulations (1272/2008/CE)

Classification Flammable liquid, category 3; Skin corrosion/irritation, category 2; Acute toxicity, category 4 (inhalation); Serious eye damage/irritation, category 2; Spec target organ tox - single, category 3

Signal word Warning

Hazard Pictograms



Hazard Statements H226, H332, H335, H315, H319
Flammable liquid and vapour. Harmful if inhaled. May cause respiratory irritation. Causes skin irritation. Causes serious eye irritation.

Precautionary Statements P210, P280, P271, P305+P351+P338, P304+P340, P403+P233, P302, P352
Keep away from heat / sparks/open flames/hot surfaces - No smoking. Wear protective gloves / protective clothing / eye protection / face protection. Use only outdoors or in a well-ventilated area. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do and continue rinsing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Store in a well ventilated place. Keep container tightly closed. IF ON SKIN: Wash with plenty of soap and water.

15.2 Chemical safety assessment

Assessment not required.

Section 16. Other Information

The information contained in this document only covers the hazards presented by this material, it DOES NOT constitute a workplace risk assessment. See sections 11 for toxicological information and section 12 for ecological information.

Revision number: 1.1 (Supersedes revision 1.0)

Revision date: 16 April 2021

Reviewed by chemist: 16 April 2021

Printed date: 25 January 2022

Copyright: 2022 SLS Select Education