





























PRODUCT DESCRIPTION

These hi-precision weighing balances are housed in an impact-resistant ABS plastic case with a stainless steel weighing pan, plastic draft shield, splash-proof membrane keypad, levelling bubble and adjustable feet. Each scale has a secondary backlit LCD display on the rear and can be either battery or mains powered via an AC/DC adapter.

- 16 selectable weighing units including g, lb, oz, ct
- Impact-resistant ABS case with adjustable feet
- Splash-proof membrane keypad incorporating 6 function keys
- 34mm hi-contrast front LCD display and 23mm hicontrast rear LCD display both with backlight
- Zero tracking ensures stable and repeatable readings
- Tare facility over the full range and can be actioned several times throughout a weighing cycle
- Plus/minus weighing
- Parts counting from 10, 20, 50 or 100 sample pieces
- Overload warning display and audible alarm
- Low battery indication
- Selectable auto power off from 3, 5 or 10 minutes of no activity or can be disabled for continuous operation
- User calibration checks with selectable weight from 1g up to the full capacity of the scale are available via certified M1 calibration weights (not supplied)
- RS-232 interface for data transfer to a PC or laptop (FHB-232 with FOC software available on our website)

TECHNICAL SPECIFICATIONS	
Capacity	600g
Resolution	0.01g
Min Pcs Wt	0.1g
Accuracy	±0.02g
Pan Size	135 x 120mm
Power	6 x 1.5V AA alkaline batteries (LR-6-6) or AC/DC mains power adaptor (supplied)
Dimensions	300 x 205 x 75 (unit) 170 x 165 x 125mm (draft shield)
Weight	1.8Kg

- Supplied with batteries, AC/DC mains power adapter, draft shield (MFHB-600) only
- 2 year warranty