# KERN EW6200-2NM

The classic balance with robust tuning fork measuring system





Measuring system				
Adjustment options:	External calibration			
Linearity:	30 mg			
Minimum weight (USP):	20 g			
Readability [d]:	10 mg			
Recommended adjusting weight:	5 kg (E2)			
Repeatability:	10 mg			
Resolution:	620000			
Stabilisation time under laboratory conditions:	3 s			
Warm up time:	4 h			
Weighing capacity [Max]:	6,200 kg			
Weighing units:	ct dwt g lb mo oz ozt tl (HK) tl (Singap. Malays) tl (Tw) tol			

### Display

Display digit height:

1,700 cm

#### Counting

Counting resolution:	620000
Mininum piece weight at piece counting (Laboratory:	10 mg
Mininum piece weight at piece counting (Normal):	100 mg

Functions				
Counting function:	yes			
Percentage determination:	yes			
Weighing with tolerance range:	yes			
Environmental conditions				
Maximum humidity:	80 %			
Maximum operating temperature:	30 °C			
Minimum ambient temperature:	10 °C			
Power supply				
Charging time:	12 h			
Input voltage:	220 V - 240 V AC 50 Hz			
Mains adapter/adapter included:	CHEURO			
n/a:	Mains adapter external			
Power supply				
Operating time (Backlight off):	32 h			
Operating time (Backlight on):	12 h			
Rechargeable battery:	Rchrg. battery optional			
Service				
Service DAkkS Certificate:	963-128			
	963-128			
DAkkS Certificate:	963-128 KERN			
DAkkS Certificate: Category				
DAkkS Certificate: Category Brand:	KERN			
DAkkS Certificate: Category Brand: Category:	KERN Balances			
DAkkS Certificate: Category Brand: Category: Product Group:	KERN Balances			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping	KERN Balances Precision balance			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery:	KERN Balances Precision balance 24 h			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH):	KERN Balances Precision balance 24 h 410 x 330 x 230 mm			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight:	KERN Balances Precision balance 24 h 410 x 330 x 230 mm 4,052 kg			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight:	KERN Balances Precision balance 24 h 410 x 330 x 230 mm 4,052 kg 2,874 kg			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method:	KERN Balances Precision balance 24 h 410 x 330 x 230 mm 4,052 kg 2,874 kg			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction	KERN Balances Precision balance 24 h 410 x 330 x 230 mm 4,052 kg 2,874 kg Parcel service			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material:	KERN Balances Precision balance 24 h 410 x 330 x 230 mm 4,052 kg 2,874 kg Parcel service Plastic			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions housing (WxDxH):	KERN Balances Precision balance 24 h 410 x 330 x 230 mm 4,052 kg 2,874 kg Parcel service Plastic 192 x 270 x 87 mm			
DAkkS Certificate: Category Brand: Category: Product Group: Packaging & shipping Delivery: Dimensions packaging (WxDxH): Gross weight: Net weight: Shipping method: Construction Casing material: Dimensions housing (WxDxH): Level indicator:	KERN Balances Precision balance 24 h 410 x 330 x 230 mm 4,052 kg 2,874 kg Parcel service Plastic 192 x 270 x 87 mm yes			

# KERN EW6200-2NM

The classic balance with robust tuning fork measuring system



### Piktogramme

#### STANDARD

CAL INT  CAL EXT	• 6000.1 RS 232	GLP PRINTER	PCS	% Percent	UNIT	-√+ ⊙ Э୬ TOL	UNDER
OPTION							
ACCU MULTI	DAkks +3 days						

FACTORY

