

HD-Lite color camera

with HDMI and USB-2 interfaces
 VC.3031

HIGHLIGHTS

- HD 1080p high definition color cameras
- Real time images directly on TV, monitor or beamer
- Stand alone or used via PC
- Built-in mouse-driven software
- C-mount interface
- HDMI, USB-2 and SD memory card
- Compatible with ImageFocus 4 software



TECHNICAL SPECIFICATIONS

| | |
|----------------------------|--|
| Sensor | HDMI 5.0 Mega pixels CMOS high sensitive sensor (Aptina) |
| Format | 1/2.5 inch, HDTV 1080p (50/60 Hz) |
| Pixels | 2592 x 1944 pixels (capture mode) 1920 x 1080 pixels (live view) HDMI 15 fps USB 15 fps |
| Video | 1080p pixels video recording mode |
| Scan mode | Progressive scan |
| Pixel size | 2.2 µm x 2.2 µm |
| Noise | 3D Noise Reduction function |
| Sensitivity | 1V |
| White balance | Automatic/manual |
| Dynamic range | 60 db |
| S/N max | 40.5 db |
| Interfaces | Digital HDMI, USB 2 |
| Storage | Standard high speed 4 Gb SD memory card or to USB-2 |
| Camera buttons | On/Off |
| Mounting | C-mount interface |
| Power supply | External main adapter 100-240 Vac to 12 Vdc/2A |
| Operation | 0 – 60° C, 45-85 % humidity |
| Storage temperature | -20 to 70° Celsius |



ON SCREEN CONTROLS (NO NEED FOR COMPUTER)

- Capture images and videos to SD
- Playback images and videos from SD
- Compare images
- Grids
- Digital zoom in/out
- Flip
- Pause
- Camera settings (white balance, color control etc)

Compatibility Suitable with ImageFocus 4 software, Windows 7 and higher

Supplied with HDMI cable, USB 2 cable, 12Vdc/2A power supply, high speed 4 Gb SD card and USB-2 mouse. Supplied with 0,45x objective. Built-in mouse-driven software for image capturing, 1080p HD video recording, image comparison and browsing of captures images and videos. Standard supplied with stage micrometer 1 mm divided in 100 parts, 10 µm per division

Product number VC.3031