

# KERN PCB 200-3



The standard in the laboratory, ideal for a wide range of applications for Industry 4.0



Recommended adjusting weight	200 g (F1)
Possible calibration points	50 g; 100 g; 200 g
Stabilization time	3 s
Warm-up time	120 min
Eccentric loading at 1/3 [Max]	0,006 g
Maximum creep (15 minutes)	10 mg
Maximum creep (30 minutes)	20 mg

Approval	
CE mark	✓

Display	
Display type	LCD
Display screen size	89×30 mm
Display backlight	✓
Display digit height	21 mm
Languages of the user interface	English Symbol language

Construction	
Dimension housing (W×D×H)	163×245×65 mm
Dimensions ring-shaped draught shield - inner (Ø×H)	90×40 mm
Dimensions completely mounted (W×D×H)	163×245×123 mm
Material display housing	Plastics
Material housing	plastic
Material weighing plate	plastic, with conductive lacquer
Material platform	Plastics
Material draught shield	plastic
Dimensions weighing surface (Ø)	82 mm
Transport safety lock - bolt torque	0,4 Nm
Levelling feet adjustable	✓

Functions	
Number of keys for operation	5
Auto-off interval(s) in mains power mode	off
Auto-off interval(s) in battery mode/rechargeable battery mode	5 min 2 min 1 min 30 min 60 min 30 sec
PreTare function	✓
Tare function	manual (multi)
Percentage determination	✓

Category	
Brand	KERN
Product category	Laboratory balance
Product group	Precision balance
Product family	PCB

Measuring System	
Construction type of the scale	Single-range balance
Weighing system	Strain gauge
Weighing capacity [Max]	200 g
Readability [d]	0,001 g
Resolution	200.000
Linearity	± 0,005 g
Reproducibility	0,001 g
Tare range	200 g
Default unit	g

kg
g
gn
dwt
tl (Tw)
tl (HK)
ozt
tl (Singap, Malays)
ct
mo
lb
oz
ffa
m

USP Minimum weight of sample (k = 2, U = 0.1%)	2 g
--	-----

Adjustment options	Adjusting with external weight
--------------------	--------------------------------

# KERN PCB 200-3



The standard in the laboratory, ideal for a wide range of applications for Industry 4.0

Counting function	✓
Tolerance weighing	✓
Tolerance weighing - type of signal	acoustically visual
Function for averaging under unstable weighing conditions	✓
Recipe/summing level	Rez A (Net total)
Underfloor weighing	Hook (included in delivery)
Interfaces	RS-232 (optional) Bluetooth (optional) Ethernet (optional) USB-Device (optional) KUP WiFi (optional)
IP protection - display	no IP protection

## Counting

Smallest piece weight when piece counting - laboratory conditions	2 mg
Smallest piece weight when piece counting - normal conditions	20 mg
Counting reference weight can be entered	✓
Reference quantity	5, 10, 20, 50, free, Input
Counting resolution (laboratory conditions)	100.000

## Power Supply

Input voltage power supply / power [Max]	100 V - 240 V AC, 50 / 60 Hz
Input voltage device / power [Max]	5,9V, 1A
Plug-in power supply type	Power adapter
Supplied power supply	Power supply unit
Plug-in power supply / adapter for countries - included with the delivery	EURO UK US CH
Plug-in power supply / adapter for countries - optional	EURO UK US CH
Rechargeable battery optional	Rchrg. battery optional - intern
Rechargeable battery charging time	8 h
Rechargeable battery operating time - backlight on	24 h
Rechargeable battery operating time - backlight off	48 h
Battery	4×1.5 V AA

Battery / accumulator type	Li-Ion
Battery connection	Battery insert
Battery operating time	20 h

## Environmental conditions

Humidity of environment [Max]	80 %
Ambient temperature [Min]	-10 °C
Ambient temperature [Max]	40 °C
Storage temperature [Min]	-20 °C
Storage temperature [Max]	60 °C

## Packing & Shipping

Readability force [d] (N)	1 d
Dimensions packaging (W×D×H)	235×365×175 mm
Net weight	0,975 kg
Shipping method	Parcel service
Net weight approx.	1,00 kg
Gross weight approx.	1,6 kg
Shipping weight	3 kg

## Services (optional)

Article number for DAkkS calibration	963-127
Article number for certificate of conformity (verification)	969-517

## Pictograms

### STANDARD



### OPTION

