ALPHA 9000 SERIES - 9030V



P3 DISPOSABLE RESPIRATOR

A traditional range of lightweight cup shape respirators offering excellent value.

KEY FEATURES

- Range tested to 'Dolomite Clogging Test (D)'
- 🔪 Soft inner nose seal
- Traditional metal nose clip adjustment
- Soft, lightweight fabrics
- Low profile valve reduces exhalation resistance keeping the wearer cooler
- Conforms to EN149: 2001 + A1 : 2009



ORDERING INFORMATION

Part Number: 9030V

- Packaging: 5 singles per box 12 boxes per case
- Certification: EN149: 2001 + A1 : 2009 FFP3 NR D

SUITABLE APPLICATIONS

Recommended applications include:

Craft work

- Cutting & Casting of Metals
- Disposal of Toxic Waste
- Hospital
- Iron & Steel Industry
- Laboratory & Disease Control
- Manufacture of Batteries (Ni-Cad)
- Mining
- Pharmaceutical Industry
- Textile Industry
- Underground Civil Engineering
- Welding Work
- Woodworking



ALPHA 9000 SERIES - 9030V

P3 DISPOSABLE RESPIRATOR

TECHNICAL SPECIFICATIONS

MATERIALS

| COMPONENT | MATERIAL |
|-------------------|--|
| Outer Cover: | Polypropylene Fabric |
| Filter Media: | High Filtration Efficiency Melt-Blown (Polypropylene) |
| Inner Cover: | Polyester Fabric |
| Nosebridge: | Aluminium |
| Nosefoam: | PVC Foam |
| Headstrap: | Knitted Elastic Band |
| Exhalation Valve: | Valve Housing - Polypropylene Valve Membrane - Synthetic Rubber |

DIMENSIONS

| ITEM | LENGTH (mm) | WIDTH (mm) | HEIGHT (mm) | |
|-------------------|------------------|---------------|----------------|--|
| Respirator: | 139 | 127 | 54 | |
| Nosebridge: | 90 | 5 | 0.5 | |
| Nosefoam: | 139 | 127 | 2 | |
| Headstrap Upper: | 540 | 10.55 | 1.5 | |
| Headstrap Lower: | 460 | 10.5 | 1.5 | |
| Exhalation Valve: | 41 (Diameter) | - | 11 | |

CERTIFICATION

EU Certification according to Regulation (EU) 2016/425 issued by: BSI Group, The Netherlands B.V., John M. Keynesplein 9, 1066 EP Amsterdam, The Netherlands. [N.B. No.2797].

RECOMMENDATIONS FOR USE

This respirator is disposable and recommended for single shift use only.

Do not attempt to clean or re-use.

PRODUCT SELECTOR GUIDANCE CHART

| Approval EN 149:2001 + A1:2009 | Product Codes | APF (Assigned Protection Factor) (x WEL) | Non-Toxic Dusts | Fine / Toxic Dusts / Mists / Fumes | Odours / Org. Vapours (Below WEL) | VeryFine / Toxic Dusts / Mists / Fumes | Metal Fumes | Oil/Water Based Particulates |
|--------------------------------------|------------------|--|--------------------|---|---|---|----------------|------------------------------------|
| FFP1 NR D | 9010 | 4 | | | | | | |
| FFP1 NR D | 9010V | 4 | | | | | | |
| FFP2 NR D | 9020 | 10 | 0 | | | | 0 | |
| FFP2 NR D | 9020V | 10 | 0 | | | | 0 | |
| FFP2 NR D | 9020W | 10 | 0 | | | | | |
| FFP3 NR | 9030V | 20 | 0 | | | | | |
| = Recommended O = Alternative | | | | | | | | |

ALPHA SOLWAY LTD, Factory 1, Queensberry Street, Annan, DG12 5BL, UK

The descriptions, characteristics, applications and photos are given for information purposes and do not constitute a contractual commitment. The manufacturer reserves the right to make any modifications it deems necessary. © 2020 Alpha Solway Ltd



