

Polyox Datasheet



Date Printed: 2016-08-01

Effective Date: 2016-07-13

Supersedes Date: 2012-04-19

Name: POLYOX

Specification Number: 000000127489

Previous Specified Material: 00126130

Final Testing Requirements

Test and Test Condition	Limit	Unit	Method	Note
Viscosity, 1% aqueous solution	1650 — 5500	cP	DOWM 101962	
pH at 25degC, 1% aqueous solution	8.0 — 10.0		DOWM 102175	
Particle Size, THRU 10 MESH, < 2000 MICRON	100 Min	%	DOWM 102261	
Particle Size, Thru 20 mesh, < 841 micron	95 Min	%	DOWM 102261	
Particle Size, THRU 60 MESH, < 250 MICRON	60 — 85	%	DOWM 102261	
Particle Size, THRU 100 MESH, < 149 MICRON	30 — 75	%	DOWM 102261	
Particle Size, THRU 200 MESH, < 74 MICRON	35 Max	%	DOWM 102261	
Particle Size, THRU 325 MESH, < 44 MICRON	25 Max	%	DOWM 102261	
Loss on Drying	0.0 — 1.0	WT%	DOWM 102188	
Alk. Earth Metals	0.0 — 1.0	WT%	DOWM 102225	

Name: POLYOX
Specification Number: 000000127489
Effective Date: 2016-07-13

Final Testing Requirements

Test and Test Condition	Limit	Unit	Method	Note
Silicon Dioxide	0.8 — 3.0	WT%	DOWM 101992	
BHT	100 — 1000	ppm wt	DOWM 102192	

General Notes

- 1 Alkaline earth metals as CaO. Volatiles - 45 min at 105C. Viscosity - Brookfield RVF, spindle 2, speed 2rpm, 25 deg C.

READ PRECAUTIONARY INFORMATION AND MATERIAL SAFETY SHEETS. THIS PRODUCT IS SHIPPED IN COMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS REGARDING CLASSIFICATION, PACKAGING, SHIPPING AND LABELING.